

Clamp meter DT-362

Technical description

Characteristic

- LCD display with backlight
- non-contact voltage detector
- AC and DC current measurement up to 400 A
- AC and DC voltage measurement up to 600 V
- low battery indication
- automatic or manual change of measuring ranges
- Data Hold and Auto Power Off functions
- double molded plastic housing

Compatibility with safety standards

- EN 61010-1 CAT III 600 V

Accessories

- test leads
- 9V battery
- type K temperature probe
- gift box with carrying case



Functions	Range	Accuracy
Voltage DC	400,0 mV	±0,8%
	4,000 V	±1,5%
	40,00 V	
	400,0 V	
Voltage AC	600,0 V	±2,0%
	400,0 mV	±1,5%
	4,000 V	
	40,00 V	
Current DC	400,0 A	±2,8%
	40,00 A	±2,5%
Current AC	400,0 A	±2,8%
	40,00 A	±2,5%
Resistance	400,0 Ω	±1,0%
	4,000 kΩ	±1,5%
	40,00 kΩ	
	400,0 kΩ	
	4,000 MΩ	±2,5%
40,00 MΩ	±3,5%	

Functions	Range	Accuracy
Capacity	40,00 nF	±1,0%
	400,0 nF	±3,0%
	4,000 μF	
	40,00 μF	
Capacity	4000 μF	±4,0%
	Frequency	10 kHz
Temperature	(-20 ÷ 760) °C	±3,0%
Jaw opening	1,2" (30 mm)	
Diode check and continuity test	YES	
Dimensions [mm]	197x70x40	
Weight [g]	183	

Ordering example

Clamp meter DT-362